



VİDANJÖR - Ürün Kodu: PRG-VAC

VACUUM/SUCTION TRUCK - Product Code: PRG-VAC

Vidanjörler, vakum pompası tarafından tank içerisinde oluşturulan güçlü emiş kuvveti ile kanalizasyon, drenaj hatları veya endüstriyel uygulamalardan kum, çamur, yağ gibi atıkların çekilmesi ve taşınması için kullanılır. Vakum, temelde bir vakum pompası ve tanktan meydana gelse de, tankın arka kapağına veya üstüne monte edilmiş emiş bomu ya da makaraları gibi hidrolik ve pnömatik bileşenler ekleyerek operatör için kullanım kolaylığı oluşturmak mümkündür. Kamyon, hooklift ya da römorklara monte edilebilmektedir. Şehrin yapısına, kanalizasyon kanallarının çaplarına, çekilen malzemenin karakterine uygun tasarlanır ve üretilirler.

Vacuum/Suction truck is used for removing and transporting sand, stones, bottles, cans, grease, sludge and other debris from sanitary sewer and/or drain lines or industrial applications, by strong suction action which is created by a vacuum pump. Although vacuum unit is basically equipped with a vacuum pump and a cylindrical debris tank, it's possible to obtain versatility by adding hydraulic and pneumatic components such as hose boom, various types of suction hose reels, assembled on the tank rear door, or on the top of it. Equipment installed upon trucks, roll on - off, trailers, and semi-trailers, suitable for liquid suction or dry suction. Designed and built according to the city's structure, sewer canals' diameters, sludge's character and mounted on 2 axle, 3 axle and 4 axle trucks with different tank and pump capacities.

OPSİYONEL ÖZELLİKLER - OPTIONS



Emiş Bomu Makarası - Mobile Arm Hose Reel



Emiş Hortumu Saklama Tamburu - Suction-Storage Hose Reel



Emiş Bomu - Suction Boom

TEKNİK ÖZELLİKLER - TECHNICAL DETAILS

Tank Kapasitesi Tank Structure	20.000 lt' ye kadar Up to 20.000 lt
Vakum Pompası Tipi Vacuum Pump Type	Fiber Bıçaklı, Blower ya da Sıvı Halkalı Rotary Vane, Blower, Centrifuge Fan or Liquid Ring
Vakum Kapasitesi Vacuum Capacity	12.000 m ³ /sa' e kadar (serbest hava) Up to 12.000 m ³ /h free air
Filtreleme Filtration	ATEX ya da çelik ATEX, steel or cartridge bags for dry suction
Pompa Tahriği Pump Drive	Ara Şanzıman ya da Hidrolik PTO, auxiliary engine or hydraulic
Kontrol Operation	Kontrol paneli, otomasyon, uzaktan kumanda, dokunmatik ekran Control panel, automation, radio remote control, touchscreen
Emiş Bomu Suction Boom	Kollu Bom ya da Emiş Makaralı Bom - 20 m hortum kapasiteli Arm boom or Mobile Arm Reel - up to 20 m hose capacity
Hortum Saklama Tamburu Storage Reel	Opsiyonel - Hidrolik kontrollü - 24 m hortum kapasiteli Optional - hydraulic driven - 24 m hose capacity
Ses İzolasyonu Sound Isolating	Opsiyonel - Ses ve sıcaklık izolasyonlu pompa kabini Optional - Isolated pump cabin



+90 312 615 52 54



info@perga.tr



Perga Machinery & Engineering



pergamakine



Gölbaşı/ANKARA



www.perga.tr