



ISLAK VE KURU ÇEKİM VİDANJÖRÜ - Ürün Kodu: PRG-JDA WET AND DRY VACUUM TRUCKS - Product Code: PRG-JDA

J-DA, toz, çamur ve sıvıların vakumla çekilmesi ve pnömatik taşınmasına yönelik çözümdür. Yüksek emiş gücü sayesinde zorlu çalışma koşullarında bile verimli sonuçlar elde eder.

%93 vakum ile 6.500 m³/saat ila 9.000 m³/saat arası debiye sahip blower pompalar ile çalışan J-DA, tankın içine yerleştirilmiş özel filtre sistemi ile, yüksek emiş verimliliği sağlar ve özel temizleme metodu ile filtre torbalarının çalışma ömrünü uzatır; hidrolik açılıp kapanan kapak ise bakımı kolaylaştırır.

Tozu filtre yuvasından tankın içine kendiliğinden boşaltmaya yönelik özel otomatik sistem, emişin kesilmesine gerek kalmadan sürekli bir akış sağlar ve böylece arıza süresini ortadan kaldırır. Özel Venturi pnömatik basınç boşaltma sistemi, tozun 60 m'ye kadar yükseklikte boşaltılmasını sağlar.

J-DA is the solution for vacuum loading and pneumatic transport of hazardous dusts, sludges and liquids. Thanks to its high suction power, it guarantees extraordinary results, even in extreme working conditions.

J-DA can also mount a vast range of vacuum pumps with flow rates of from 6,500 m³/h to 9,000 m³/h with a maximum vacuum of 93%. The special filter housing incorporated in the tank guarantees perfect suction efficiency and extends the working life of the filter bags, while the cover with hydraulic opening and closing simplifies maintenance. The exclusive automatic system for self-discharging the dust from the filter housing into the tank maintains a continuous flow without having to interrupt suction, thus eliminating down time.

The exclusive Venturi pneumatic pressure offloading system enables the dust to be offloaded at a height of up to 60 m.

TEKNİK ÖZELLİKLER - TECHNICAL DETAILS

| | |
|---------------------------------------|--|
| Tank Hacmi Tank Volume | 8 m ³ - 12 m ³ 8 m ³ - 12 m ³ |
| Vakum Pompası Vacuum Pump | Blower, 9.000 m ³ /h'e kadar (serbest hava) Blower, up to 9.000 m ³ /h (free air) |
| Hava Kompresörü Air Compressor | 1.5 m ³ /dk, 8 bar 1.5 m ³ /min, 8 bar |
| Filtreleme Filtration | Otomatik Automatic |
| Emiş Bomu Suction Boom | 8" Kollu Katlanır Bom 8" Folding Arm Boom |
| Pompa Tahriği Pump Drive | NMW ya da Ara Şanzıman PTO NMW or Split PTO |
| Kontrol Operation | Kontrol paneli, otomasyon, uzaktan kumanda, dokunmatik ekran Control panel, automation, wireless or HMI |
| Ses İzolasyonu Sound Isolation | Opsiyonel - Ses İzolasyonu Optional - Sound Isolation |
| Damper Boşaltma Telescopic Lifting | 55°'ye kadar Up to 55° |



+90 312 615 52 54



info@perga.tr



Perga Machinery & Engineering



pergamakine



Gölbaşı/ANKARA



www.perga.tr