



ABD TİPİ KOMBİNE KANAL AÇMA ARACI - Ürün Kodu: PRG-USA US-VAC COMBI SEWER CLEANERS - Product Code: PRG-USA

Kombine kanal açma ve temizleme aracı, vakum pompası, yüksek basınçlı su pompası ve kanaldan çekildten malzemenin depolandığı silindirik bir tanktan oluşur. Vakum özelliği yanında, kanal hatlarının yüksek basınçlı suyla yıkanmasını, tıkanıklıkların giderilmesini ve kanalizasyon rögarlarının temizlenmesini sağlar. Şehrin yapısına, kanalizasyon kanallarının çaplarına, çekilen malzemenin karakterine uygun tasarlanır ve üretilirler. Farklı tank ve pompa kapasitelerine göre 2 akslı, 3 akslı ve 4 akslı kamyonlar üzerine monte edilebilmektedir.

ABD TİPİ KOMBİNE KANAL AÇMA ARACI, Amerika standartlarına uygun olarak tasarlanmış araçlardır.

US-VAC Combi jetting and vacuum truck has a vacuum pump and a high-pressure water pump. It is equipped with a self-contained water supply as the water source for the high-pressure pump and a cylindrical debris tank for collecting all materials coming from the sewer system. It is also able to perform simultaneous high-pressure flushing of sewer pipes and removal of liquids and solids from the sewer manhole. Designed and built according to the city's structure, sewer canals' diameters, and sludge's character and mounted on 2 axles, 3 axle, and 4 axle trucks with different tank and pump capacities.

US-VAC COMBI SEWER CLEANERS are designed for USA market. There are telescopic boom, front jetting hose reel, side clean water tanks and water transformer, which are regular specifications of USA trucks.

TEKNİK ÖZELLİKLER - TECHNICAL DETAILS



Tank Kapasitesi Tank Structure	14.000 lt'ye kadar - Yan paslanmaz tanklar Up to 14.000 lt with side clean water tanks
Yüksek Basınç Pompası(Transformer) Water Transformer	200 bar'a kadar, 500 lpm debide Up to 200 bars, 500 lpm
Vakum Pompası Tipi Vacuum Pump Type	Fiber Bıçaklı, Blower ya da Sıvı Halkalı Rotary Vane, Blower or Liquid Ring
Vakum Kapasitesi Vacuum Capacity	11.000 m ³ /sa' e kadar (serbest hava) Up to 11.000 m ³ /h free air
Filtreleme Filtration	ATEX, çelik ya da kuru emişe uygun filtre torbası (kartuş) ATEX, steel or cartridge bags for dry suction
Pompa Tahrifiği Pump Drive	Ara Şanzıman ya da Hidrolik PTO or Hydraulic
Kanal Açma Makarası Hydraulic Hose Reel	Ön Kısma monteli açılır, hız kontrollü, 120 m hortum kapasiteli Front mounted rotating, with speed adjutmnet, up to 120 m hose
Yardımcı Makara Auxiliary Hose Reel	Manuel ya da Hidrolik, 80 m hortum kapasiteli Manual or hydraulic, up to 80 m hose
Kontrol Operation	Kontrol paneli, otomasyon, uzaktan kumanda, dokunmatik ekran Control panel, automation, radio remote control, touchscreen
Emiş Bomu Suction Boom	Teleskopik Kollu Bom Telescopic arm boom
Ses İzolasyonu Sound Isolating	Opsiyonel - Ses ve sıcaklık izolasyonlu pompa kabini Optional - Isolated pump cabin

