



## ŞAMANDIRA - Ürün Kodu: PRG-PSO

### PRIMARY SHUTOFF - Product Code: PRG-PSO

#### Ürün Detayları

Şamandıralar, vakum hattının başladığı makineye kaynaklanacak şekilde tasarlanmıştır. Paslanmaz çelik, yüzer bilyeli bir "taşma" sistemi ile donatılmıştır. Bu sistem emilen malzemenin (sıvı vb.) tank içerisinde maksimum seviyeye ulaştığında vakum hattına girmesini engeller. Şamandıralar, vakum kesici ve emniyet valfleri, basınç göstergeleri ve havalandırma sistemleri ve siklon drenajları gibi çeşitli aksesuarların bağlanmasını sağlayan bir dizi yan kaplin ile donatılmıştır.

#### Product Details

The opening primary shutoffs are designed to be welded to the machine, where the vacuum line starts. The primary shutoffs are equipped with an "overflow" system with a stainless steel floating ball. This system prevents the suctioned material (liquids or similar) from entering the vacuum line when the maximum level inside the tank is reached. The opening primary shutoffs are equipped with a series of side couplings that enable the connection of various types of accessories, such as vacuum breaker and safety valves, pressure gauges and vent systems and cyclone drains.

#### TEKNİK ÖZELLİKLER - TECHNICAL DETAILS

Emiş Hattı Çapı Vacuum Diameter	4" - 5" - 6" 4" - 5" - 6"
Gövde Malzemesi Body Material	ST37 ya da SS304 ST37 or SS304
Maks. Basınç Max. Pressure	4 Bar 4 Bar
Min. Basınç Min. Pressure	-1 Bar -1 Bar

